CLAIMS

What is claimed is:

- 1. A prosthetic heart valve comprising:
- a polymeric valve body having at least one leaflet, said leaflet having an open position and a closed position,
- a stent coupled to said valve body, said stent having a plurality of apertures, said
 apertures being exposed outside said polymeric valve body.
 - 2. The prosthetic heart valve of claim 1 wherein said stent comprises a base circumferentially disposed around said valve body and wherein said apertures penetrate said base.
 - 3. The prosthetic heart valve of claim 2 wherein said polymeric valve body encloses said base and includes a plurality of apertures in said polymeric valve body corresponding to said apertures in said base.
 - 4. The prosthetic heart valve of claim 2 wherein said polymeric valve body encloses only a portion of said base, said portion not including said plurality of apertures in said base.
 - 5. The prosthetic heart valve of claim 2 wherein said stent comprises a plurality of commissures in generally cylindrical configuration and said base is connected to said commissures at an upstream location and said base slants radially outwardly from said commissures.
 - 6. The prosthetic heart valve of claim 5 wherein a junction between said commissures and said base forms an angle of between 90° and 135°.
 - 7. The prosthetic heart valve of claim 2 further comprising a sewing ring circumferentially surrounding the valve body.

CMI-425

- 8. The prosthetic heart valve of claim 7 wherein said sewing ring is connected to said base at an upstream, inner side of said base.
- 9. The prosthetic heart valve of claim 2 wherein at least some of said apertures are slots.
- 10. The prosthetic heart valve of claim 9 wherein at least one of said apertures is generally circular.
- 11. The prosthetic heart valve of claim 1 further comprising a sewing ring circumferentially surrounding the valve body and the stent and attached to the stent by fasteners extended through said apertures in said stent.
- 12. The prosthetic heart valve of claim 11 wherein the fasteners are sutures.
- 13. The prosthetic heart valve of claim 1 wherein said stent further comprises an upstream edge and a wire connected to said edge wherein the suture apertures are downstream from said wire.
- 14. The prosthetic heart valve of claim 13 further comprising a sewing ring circumferentially surrounding the valve body and the stent and attached to the stent by fasteners extended through said apertures in said stent.
- 15. The prosthetic heart valve of claim 14 wherein the fasteners are sutures.
- 16. The prosthetic heart valve of claim 2 wherein the ring comprises a fabric reenforcement.
- 17. A prosthetic heart valve comprising:
- a polymeric valve body having at least one leaflet, said leaflet having an open position and a closed position, CMI-425

a stent molded within said valve body, said stent having a plurality of apertures, said apertures being exposed through said polymeric valve body.

- 18. The prosthetic heart valve of claim 17 wherein said stent comprises a base circumferentially disposed around said valve body and wherein said apertures penetrate said base.
- 19. The prosthetic heart valve of claim 18 wherein said polymeric valve body encloses said base and includes a plurality of apertures in said polymeric valve body corresponding to said apertures in said base.
- 20. The prosthetic heart valve of claim 18 wherein said polymeric valve body encloses only a portion of said base, said portion not including said plurality of apertures in said base.
- 21. The prosthetic heart valve of claim 18 wherein said stent comprises a plurality of commissures in generally cylindrical configuration and said base is connected to said commissures at an upstream location and said base slants radially outwardly from said commissures.
- 22. The prosthetic heart valve of claim 21 wherein a junction between said commissures and said base forms an angle of between 90° and 135°.
- 23. The prosthetic heart valve of claim 18 further comprising a sewing ring circumferentially surrounding the valve body.
- 24. The prosthetic heart valve of claim 23 wherein said sewing ring is connected to said base at an upstream, inner side of said base.
- 25. The prosthetic heart valve of claim 18 wherein at least some of said apertures are slots.

 CMI-425

- 26. The prosthetic heart valve of claim 25 wherein at least one of said apertures is generally circular.
- 27. The prosthetic heart valve of claim 17 further comprising a sewing ring circumferentially surrounding the valve body and the stent and attached to the stent by fasteners extended through said apertures in said stent.
- 28. The prosthetic heart valve of claim 27 wherein the fasteners are sutures.
- 29. The prosthetic heart valve of claim 17 wherein said stent further comprises an upstream edge adjacent blood flowing into the valve and a wire connected to said upstream edge wherein the suture apertures are downstream from said wire.
- 30. The prosthetic heart valve of claim 29 further comprising a sewing ring circumferentially surrounding the valve body and the stent and attached to the stent by fasteners extended through said apertures in said stent.
- 31. The prosthetic heart valve of claim 30 wherein the fasteners are sutures.
- 32. The prosthetic heart valve of claim 29 wherein said stent further comprises a base, said base having a downstream edge, and said apertures being in said base, and being closer to said downstream edge than to said upstream edge.
- 33. The prosthetic heart valve of claim 18 wherein the ring comprises a fabric reenforcement.